



IRAN PARAFFIN CO.  
(Ltd.)

## Liquid Paraffin Laminex 14

Our Liquid Paraffin (Laminex 14) is totally transparent and odorless. The company can produce liquid paraffin with different flash points , according to customer orders.

**Application:** Glasswork - Candle Making - Weaving - Agriculture Pesticides - Plastics &...

**Packaging:** 200-liter steel drum - Tanker

## Specification of LAMINNEX 14

Items	Results	Test Method
Kin viscosity: At 40 °C At 100 °C	5 - 6.5 Cst 1 - 1.5 Cst	ASTM D-445 ASTM D-445
Pour point (Max) (°C)	0	ASTM D-97
Flash point (Min) (°C)	135 -142	ASTM D-92
Specific gravity (kg/L)	0.82 - 0.80	ASTM D-1298
Colour sybolt	25 - 30	ASTM D-156
Sulfur content wt (%)	0.01 - 0.002	ASTM D-129
Carbon residue wt (%)	0.001 - 0.005	ASTM D-189
Aromatic mass (%)	0.005 - 0.001	ASTM Calcul.
I.B.P (°C)	270	ASTM D86
F.B.P (°C)	390	ASTM D86

Unit 4 & 8 - No. 1719 - After gas station - North Amirabad St. - Tehran - Iran

Phone & Fax: +98 21 8833 7696 and 99

Email: [info@iranparafin.com](mailto:info@iranparafin.com)

Postal Code: 1413653377

web site: [www.iranparafin.com](http://www.iranparafin.com)