



IRAN PARAFFIN CO.
(Ltd.)

Liquid Paraffin Laminex 20

Liquid Paraffin (Laminex 20) of Iran Paraffin Company's totally transparent and odorless. The company can produce liquid paraffin with different flammable temperature, according to customer requirements.

Application: Glasswork - Candle Making - Weaving - Agriculture Pesticides - Plastics &...

Packaging: 200-liter steel drum - Tanker

Specification of LAMINNEX 20

Items	Results	Test Method
Kin viscosity: At 40 °C	16-20 Cst	ASTM D-445
At 100 °C	3.2-4.0 Cst	ASTM D-445
Pour point(Max)	-18 °C	ASTM D-97
Flash poi	190- 200 °C	ASTM D-92
Specific gravity	0.800-0.850	ASTM D-1298
Colour sybolt	28-30	ASTM D-156
Sulfur content wt %	0.002-0.01	ASTM D-129
Carbon residue wt %	0.001-0.005	ASTM D-189
Aromatic mass %	0.1-0.5	ASTM Calcul.
I.B.P	390°C	ASTM D86
F.B.P	470°C	ASTM D86

Unit 4 & 8 - No. 1719 - After gas station - North Amirabad St. - Tehran - Iran

Phone & Fax: +98 21 8833 7696 and 99

Email: info@iranparafin.com

Postal Code: 1413653377

web site: www.iranparafin.com